

SPEED PAN-TILT-UNIT "ROTOR HEAD" FOR MOBOTIX CAMERAS

Product number: 70004P0000008
 Date: August 2017



FEATURES

This are our NEW MX PT5 Types with built-in RS 232- USB interface and internal cabling CAT-Cable (5m) for MOBOTIX cameras

Type of Camera:

M15/ M16, M24/ M25,/ M26 S14/ S15 and S16 are supported . (housing for S Series is extra to order)

The high-speed pan-tilt head features precision 12VDC stepper motors. It needs no mechanical stops due to sliding contacts.

Programing of enless Tours is one of the newest Features

PT5 is already integrated in to the *MX Control Center* ® and MX Software. So it is controllable by browser.

Additional IR Illuminators with 12V DC are supported

Two types of Power sources are available:

- 24V AC/DC power with additional power supply
- Complete PoE option (with 30w PoE Injector)

TECHNICAL SPECIFIKATION

Warranty:	2 years
Positions:	32 fixed positions
Rotation:	pan +360°, tilt -80° - +13°
Usability:	indoor and outdoor
Construction:	die-cast aluminum
Mounting accessories:	variety of accessories
Weatherproof:	to IP66
Capacity:	3,5 kg / 7,7 pounds
Swivel range:	360° endless at 8° per second
Power demand:	9W Operation, 5W Standby 24V AC/DC (without camera)
Temperature range:	-25°C to +60°C -9 to +140 Fahrenheit
Dimensions:	275x190x165 mm
12V DC exit for IR/ white light illuminators	
Bracket optional for IR/white light illuminator	
Comes with power adapter (for the head and a camera),	
Upgrade to PoE with 20W PoE Injector	

ACCESSORIES

Delivery without camera and bracket



Technical Drawing

Technical Drawing Bracket

